

Page 1 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

**Safety data sheet
 according to Regulation (EC) No 1907/2006, Annex II**

P302+P352-IF ON SKIN: Wash with plenty of water / soap. P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313-IF exposed or concerned: Get medical advice / attention.

EUH204-Contains isocyanates. May produce an allergic reaction.

4,4'-methylenediphenyl diisocyanate
 2,2'-methylenediphenyl diisocyanate
 o-(p-isocyanatobenzyl)phenyl isocyanate
 Diphenylmethanediisocyanate, isomeres and homologues

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ALU-RAPID P860

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive
 Sector of use (SU):
 SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Bertec BVBA, Tulpenstraat 3, B-9810 Eke – Nazareth
 Phone: +32(0)9 380 38 85, Fax: +32(0)9 380 18 23
info@bertec.be, www.bertec.be

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

112

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Propylene carbonate	
Registration number (REACH)	01-2119537232-48-XXXX
Index	607-194-00-1
EINECS, ELINCS, NLP	203-572-1
CAS	108-32-7
content %	1<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319

Diphenylmethanediisocyanate, isomeres and homologues	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	---
CAS	9016-87-9
content %	1<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)

4,4'-methylenediphenyl diisocyanate	
Registration number (REACH)	01-2119457014-47-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP	202-966-0
CAS	101-68-8
content %	1<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)

o-(p-isocyanatobenzyl)phenyl isocyanate	
Registration number (REACH)	01-2119480143-45-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP	227-534-9
CAS	5873-54-1
content %	1<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)

2,2'-methylenediphenyl diisocyanate	
Registration number (REACH)	01-2119927323-43-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP	219-799-4
CAS	2536-05-2
content %	0,1<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

P201-Obtain special instructions before use. P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P284-Wear respiratory protection.

Page 2 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.
 Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.
 Dab away with polyethylene glycol 400

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

- The following may occur:
- Dermatitis (skin inflammation)
 - Drying of the skin.
 - Allergic contact eczema
 - Discoloration of the skin
 - Irritant to mucosa of the nose and throat
 - Coughing
 - Headaches
 - Effect on the central nervous system
 - Asthmatic symptoms
 - In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.
 - Respiratory distress

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

In case of irritation of the lungs, perform first-aid with controlled-dosage aerosol dexamethasone.
 Pulmonary oedema prophylaxis
 Medical supervision necessary due to possibility of delayed reaction.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

- CO2
- Extinction powder
- Water jet spray
- Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

- Oxides of carbon
- Oxides of nitrogen
- Isocyanates
- Hydrocyanic acid (hydrogen cyanide)
- Toxic gases
- Danger of bursting (explosion) when heated

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
 Protective respirator with independent air supply.
 According to size of fire
 Full protection, if necessary.
 Cool container at risk with water.
 Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.
 Avoid inhalation, and contact with eyes or skin.
 If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.
 Resolve leaks if this possible without risk.
 Prevent surface and ground-water infiltration, as well as ground penetration.
 Prevent from entering drainage system.
 If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.
 Allow to stand for a few days in an unclosed container until reaction no longer occurs.
 Keep moist.
 Do not close packing drum.
 CO2 formation in closed tanks causes pressure to rise.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid inhalation of the vapours.
 If applicable, suction measures at the workstation or on the processing machine necessary.
 Avoid contact with eyes or skin.
 No contact with products of this type in case of allergies, asthma and chronic respiratory tract disorders.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingsuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Keep protected from direct sunlight and temperatures over 50°C.
 Only store at temperatures from to .
 Store in a dry place.

7.3 Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues		Content %:1-<10
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	---
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)		Other information: Sen (Isocyanates, all (as -NCO))	

Chemical Name	4,4'-methylenediphenyl diisocyanate		Content %:1-<10
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	---
Monitoring procedures: ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenyl)piperazine and liquid chromatography) - 2001 MDHS 25/3 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1-methoxyphenyl)piperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 1999 - EU project BC/CEN/ENTR/000/2002-16 card 7-4 (2004)			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)		Other information: Sen (Isocyanates, all (as -NCO))	

Chemical Name	o-(p-isocyanatobenzyl)phenyl isocyanate		Content %:1-<10
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	---
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)		Other information: Sen (Isocyanates, all (as -NCO))	

Chemical Name	2,2'-methylene-diphenyl diisocyanate		Content %:0,1-<1
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	---
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)		Other information: Sen (Isocyanates, all (as -NCO))	

Chemical Name	Titanium dioxide		Content %:
WEL-TWA: 10 mg/m3 (total inhalable dust), 4 mg/m3 (respirable dust)	WEL-STEL: ---	---	---
Monitoring procedures: ---			
BMGV: ---		Other information: ---	

Chemical Name	4,4'-methylenediphenyl diisocyanate		Content %:
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	---
Monitoring procedures: ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenyl)piperazine and liquid chromatography) - 2001 MDHS 25/3 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1-methoxyphenyl)piperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 1999 - EU project BC/CEN/ENTR/000/2002-16 card 7-4 (2004)			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)		Other information: Sen (Isocyanates, all (as -NCO))	

Chemical Name	Silica, amorphous		Content %:
WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---	---
Monitoring procedures: ---			
BMGV: ---		Other information: ---	

Chemical Name	o-(p-isocyanatobenzyl)phenyl isocyanate		Content %:
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	---
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)		Other information: Sen (Isocyanates, all (as -NCO))	

Chemical Name	Calcium carbonate		Content %:
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---	---	---
Monitoring procedures: ---			
BMGV: ---		Other information: ---	

Chemical Name	Diphenylmethanediisocyanate, isomeres and homologues		Content %:
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO))	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO))	---	---
Monitoring procedures: ---			
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure)		Other information: Sen (Isocyanates, all (as -NCO))	

Propylene carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sporadic (intermittent) release		PNEC	9	mg/l	

Page 3 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

	Environment - marine		PNEC	0,09	mg/l	
	Environment - sediment, marine		PNEC	0,083	mg/l	
	Environment - soil		PNEC	0,81	mg/l	
	Environment - freshwater		PNEC	0,9	mg/l	
	Environment - sediment, freshwater		PNEC	0,83	mg/l	
	Environment - sewage treatment plant		PNEC	7400	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	25	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,5	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	176	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	50	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	20	mg/m3	

4,4'-methylenebis(phenyl) diisocyanate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm ²	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm ²	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	

o-(p-isocyanatobenzyl)phenyl isocyanate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm ²	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	

Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm ²	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

2,2'-methylenebis(phenyl) diisocyanate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm ²	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm ²	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

Titanium dioxide

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

4,4'-methylenebis(phenyl) diisocyanate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/d	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm ²	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm ²	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

Page 4 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

o-(p-isocyanatobenzyl)phenyl isocyanate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - soil		PNEC	1	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	1	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg body weight/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm ²	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm ²	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

Diphenylmethanediisocyanate, isomers and homologues

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	1	mg/kg	
Consumer	Human - oral	Short term, local effects	DNEL	20	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm ²	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm ²	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/d	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. BS EN 14042.
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedings.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN 374).
 Recommended
 Protective nitrile gloves (EN 374).
 Minimum layer thickness in mm:
 >= 0,35
 Permeation time (penetration time) in minutes:
 >= 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Filter A2 P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Pastelike, Liquid
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	~ 1,52 g/cm ³ (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

reacts with water

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Exothermic reaction possible with:

Alcohols
 Amines
 Bases
 Acids
 Water

Development of:
 Carbon dioxide
 CO₂ formation in closed tanks causes pressure to rise.
 Pressure increase will result in danger of bursting.

10.4 Conditions to avoid

Protect from humidity.
 Polymerisation due to high heat is possible.

Page 5 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

T > ~ 260°C
10.5 Incompatible materials

Acids
 Bases
 Amines
 Alcohols
 Water

10.6 Hazardous decomposition products
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Alu-Rapid P860

Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			Vapours, calculated value
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Propylene carbonate

Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Human being		No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 482 (Gen. Tox. - DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative
Carcinogenicity:				Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative

Aspiration hazard:						No
Symptoms:						breathing difficulties, headaches, gastrointestinal disturbances, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOEL	>5000	mg/kg		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOEC	100	mg/m ³		OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Dust, Mist

Diphenylmethanediisocyanate, isomers and homologues

Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	0,31	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Expert judgement.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion, Does not conform with EU classification.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Respiratory or skin sensitisation:				Rat		Yes (inhalation)
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Limited evidence of a carcinogenic effect.
Reproductive toxicity:	NOAEL	4	mg/m ³	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Aspiration hazard:						Negative
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, May cause respiratory irritation.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive

4,4'-methylenebisphenyl diisocyanate

Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol, Expert judgement.

Page 6 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

Acute toxicity, by inhalation:	LC50	0,368	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2. Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion, Does not conform with EU classification.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact)
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Rat	OECD 489 (In Vivo Mammalian Alkaline Comet Assay)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Limited evidence of a carcinogenic effect., Aerosol, Analogous conclusion
Reproductive toxicity:	NOEL	4	mg/m ³	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	0,2	mg/m ³	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	LOEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive

o-(p-isocyanatobenzyl)phenyl isocyanate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	0,387	mg/l/4h	Rat		Aerosol, Does not conform with EU classification.
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Aerosol, Expert judgement.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2. Analogous conclusion

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion, Does not conform with EU classification.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation), Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion, Limited evidence of a carcinogenic effect.
Reproductive toxicity:	NOEL	4	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	LOEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEL	0,2	mg/m ³	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Symptoms:						mucous membrane irritation, breathing difficulties, coughing, asthmatic symptoms
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory system, Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system, Positive

2,2'-methylenebis(phenyl diisocyanate)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation), Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Limited evidence of a carcinogenic effect., Analogous conclusion, Aerosol
Reproductive toxicity:	NOEL	4	mg/m ³	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect., Aerosol, Analogous conclusion

Page 7 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	1		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	0,2		Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion
Symptoms:						respiratory distress, coughing, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						May cause respiratory irritation.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): respiratory system

Titanium dioxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract).
Symptoms:						coughing, Irritant to mucosa of the nose and throat
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		90d
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	10	mg/m ³	Rat		90d

4,4'-methylenebis(phenyl diisocyanate)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	

Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>2,24	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	0,368	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant, Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (inhalation and skin contact), Analogous conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Limited evidence of a carcinogenic effect.
Reproductive toxicity:	NOAEL	4	mg/m ³	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Symptoms:						respiratory distress, coughing, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract, Target organ(s): respiratory system

Silica, amorphous						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No

o-(p-isocyanatobenzyl)phenyl isocyanate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	0,387	mg/l/4h	Rat		Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant, Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (inhalation), Analogous conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion

Page 8 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Limited evidence of a carcinogenic effect.
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Symptoms:						asthmatic symptoms, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Target organ(s): respiratory tract, Irritant

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixed Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative, administered as Calcium carbonate
Reproductive toxicity:						Negative, administered as Calcium carbonate

Diphenylmethanediisocyanate, isomers and homologues						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	0,49	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Germ cell mutagenicity:					OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:		1	mg/m ³	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Positive
Reproductive toxicity:	NOAEL	12	mg/m ³	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Aerosol
Reproductive toxicity (Developmental toxicity):		4		Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative

Reproductive toxicity (Effects on fertility):					Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):							Irritation of the respiratory tract
Specific target organ toxicity - repeated exposure (STOT-RE):	NOEC	0,2	mg/kg			OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	
Aspiration hazard:							No
Symptoms:							fever, coughing, headaches, nausea and vomiting, dizziness, breathing difficulties, laryngeal oedema, oedema of the lungs, chemical pneumonitis (condition similar to pneumonia), abdominal pain, diarrhoea
Specific target organ toxicity - single exposure (STOT-SE), inhalative:							Target organ(s): respiratory organs, May cause respiratory irritation.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

COSMO PU-100.130
COSMO PU-100.131
COSMO PU-100.132
COSMO PU-100.140

(COSMOPUR 819)
(COSMOPUR 819 schwarz)
(COSMOPUR 819 grau)
(COSMOPUR 819 C)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide). According to experience available to date, polycarbamide is inert and non-degradable.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Propylene carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Cyprinus caprio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Page 9 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P 860

12.1. Toxicity to algae:	EC50	72h	>900	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			83,5-87,7	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable 29d
12.2. Persistence and degradability:	DOC	14d	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	
12.3. Bioaccumulative potential:	Log Pow		-0,48				Bioaccumulation is unlikely (LogPow < 1), calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	25619	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other information:	AOX		0	%			Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Diphenylmethanediisocyanate, isomers and homologues							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other organisms:	NOEC/N OEL	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/N OEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (III))	Not biodegradable
12.3. Bioaccumulative potential:	BCF	42d	<14		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	No significant biodegradation is expected.
12.5. Results of PBT and vPvB assessment							Negative
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/N OEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	

Toxicity to annelids:	NOEC/N OEL	14d	>1000	mg/kg	Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	
-----------------------	------------	-----	-------	-------	----------------------	--	--

4,4'-methylenebis(phenyl isocyanate)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other information:	H (Henry)		0,0229				
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/N OEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (III))	Not biodegradable
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	IUCLID Chem. Data Sheet (ESIS)	Not to be expected
12.3. Bioaccumulative potential:	Log Pow		5,22				A notable biological accumulation potential has to be expected (LogPow > 3).
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to annelids:	EC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion
Toxicity to annelids:	NOEC/N OEL	14d	>1000	mg/kg	Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion
Water solubility:							According to experience available to date, polycarbamide is inert and non-degradable. With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide).

o-(p-isocyanatobenzyl)phenyl isocyanate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected, Analogous conclusion
Other organisms:	NOEC/N OEL	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion

Page 10 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

Other organisms:	NOEC/N OEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other information:	H (Henry)		0,0229				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/N OEL	21d	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, Analogous conclusion
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Toxicity to annelids:	NOEC/N OEL	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

2,2'-methylenebis(4-chlorophenyl) diisocyanate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/N OEL	21d	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion

12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide). According to experience available to date, polycarbamide is inert and non-degradable. Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		5,22				A notable biological accumulation potential has to be expected (LogPow > 3).
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

Titanium dioxide

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriella subcapitata	U.S. EPA-600/9-78-018	
12.3. Bioaccumulative potential:	BCF	14d	19-352				Oncorhynchus mykiss
12.3. Bioaccumulative potential:	BCF	42d	9,6				No
12.4. Mobility in soil:							Negative
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas fluorescens		
Toxicity to annelids:	NOEC/N OEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble 20 °C

4,4'-methylenebis(4-chlorophenyl) diisocyanate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC0	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	1,5	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/N OEL	72h	1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion

Page 11 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide)., According to experience available to date, polycarbamide is inert and non-degradable.
12.2. Persistence and degradability:	BOD	28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide)., According to experience available to date, polycarbamide is inert and non-degradable.
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	Log Pow		5,22				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Toxicity to annelids:	EC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

Silica, amorphous							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	EC0	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC0	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	ErC50	72h	>=10000	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

o-(p-isocyanatobenzyl)phenyl isocyanate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO ₂ into a firm, insoluble reaction product with a high melting point (polycarbamide)., Analogous conclusion
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected, Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000		Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

Calcium carbonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	

Page 12 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
Water solubility:			0,014	g/l			

Diphenylmethanediisocyanate, isomers and homologues

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	0	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Not biodegradable
12.3. Bioaccumulative potential:	BCF	42d	<14		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other information:	BOD	28d	<10	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:
 The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances
 08 05 01 waste isocyanates
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 E.g. suitable incineration plant.
 Hardened product:
 E.g. dispose at suitable refuse site.
For contaminated packing material
 Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.
 15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

14.1. UN number: n.a.
Transport by road/by rail (ADR/RID)
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Classification code: n.a.
 LO: n.a.
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code:
Transport by sea (IMDG-code)
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable
Transport by air (IATA)
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)
 Regulation (EC) No 1907/2006, Annex XVII
 Diphenylmethanediisocyanate, isomers and homologues
 4,4'-methylenebis(phenyl diisocyanate)
 o-(p-isocyanatobenzyl)phenyl isocyanate
 2,2'-methylenebis(phenyl diisocyanate)
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8

These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).
 H373 May cause damage to organs through prolonged or repeated exposure by inhalation.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.

Page 13 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 11.09.2021 / 0010
 Replacing version dated / version: 25.04.2019 / 0009
 Valid from: 11.09.2021
 PDF print date: 11.09.2021
 Alu-Rapid P860

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.

Eye Irrit. — Eye irritation
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
 Skin Irrit. — Skin irritation
 Resp. Sens. — Respiratory sensitization
 Skin Sens. — Skin sensitization
 Carc. — Carcinogenicity
 STOT RE — Specific target organ toxicity - repeated exposure
 Acute Tox. — Acute toxicity - inhalation

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.